

## Very resistant plastic hinges reinforced with CFT fiberglass.

Very resistant plastic hinges reinforced with CFT fiberglass.

[Catalog access](#)

Very resistant plastic hinges reinforced with CFT fiberglass.

### Technical information

Código	Elementos standard	Código	Descripción	Dimensiones principales							Agujero roscado					Peso g		
				L	B	f	f1	H	h1	b1	d	d3	d4	h3	h4		d6	C [Nm] #
	427111-C9		CFT.40 EH-4-C9	39.5	38	25	25	13	9	17.5	3	4.5	-	4	-	7	2	11
	427112-C9		CFT.40 SH-4-C9	39.5	38	25	25	13	9	17.5	3	4.5	8.5	-	4.5	-	2	11
	427131-C9		CFT.49 EH-5-C9	49.5	48	30.5	31	16.5	11.5	21.5	4	5.5	-	5	-	8.5	2	24
	427132-C9		CFT.49 SH-5-C9	49.5	48	30.5	31	16.5	11.5	21.5	4	5.5	10.5	-	5	-	2	24
	427133-C9 *		CFT.49 EH-6-C9 *	49.5	48	30.5	31	16.5	11.5	21.5	4	6.5	-	5	-	10	2	24
	427151-C9		CFT.65 EH-6-C9	65	63	40	40	21.5	15	29	5	6.5	-	7	-	10	2	50
	427152-C9		CFT.65 SH-6-C9	65	63	40	40	21.5	15	29	5	6.5	12.5	-	7.5	-	2	50