

## End Caps, ISO

**Manufacturing Standards:** ISO-1127-dimensional accessories manufactured for welding according to ISO DIN-2605/17457

**Grade:** Austenitic series 304-L, 316-L


**Finishes:** Standard finish 2B

**Dimensions:** Manufactured in diameters from 17.2 mm to 456.2 mm

**Certificates:** Product certificates provided, if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

**Tolerances:** Allowable Differences in diameter and eccentricity + - 1.0% and thickness of + - 15%

**Applications:** Primarily used to construct pipes or tubes, as conductors of fluids (gases, liquids, slurries and solids in powder state).



### Technical information

DN	Ø		Dimensiones		Calidades AISI	
	Nominal en Pulgadas	D	E	A aprox	304-L	316-L
15	1/2"	21.3	2	0.023	x	x
20	3/4"	26.9	2	0.02	x	x
25	1"	33.7	2	0.02	x	x
32	1 1/4"	42.4	2	0.036	x	x
40	1 1/2"	48.3	2	0.51	x	x
50	2"	60.3	2	0.066	x	x
65	2 1/2"	76.1	2	0.124	x	x
80	3"	88.9	2	0.138	x	x
100	4"	114.3	2	0.2	x	x
125	5"	139.7	2	0.269	x	x
150	6"	168.3	2	0.378	x	x
200	8"	219.1	2	0.618	x	x
250	10"	273	2	0.906	x	x
300	12"	323.9	3	1.963	x	x
350	14"	355.6	3	2.773	x	x
400	16"	406.4	3	4.172	x	x

450	18"	457.2	3	5.204	x	x
-----	-----	-------	---	-------	---	---