

## End Caps, Metric

**Manufacturing Standards:** Welded millimetric components are manufactured according to DIN-2605/17457 standards.


**Grade:** Austenitic, series 304, 316, 304-L, 316-L.

**Finishes:** Standard finish 2B demand, satin or polished.

**Dimensions:** Manufactured in diameters from 18 mm to 506 mm.

**Certificates:** Product certificates provided, if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

Image not found or type unknown



### Technical information

DN	Dimensiones			Peso kgs	Calidades	
	D	E	A aprox		AISI-304L	AISI-316L
15	18	2	13	0.01	x	x
	20	2	13	0.012	x	x
20	23	2	15	0.014	x	x
	25	2	15	0.015	x	x
25	28	2	11	0.022	x	x
	30	2	11	0.023	x	x
32	33	2	12	0.025	x	x
	38	2	12	0.032	x	x
40	43	2	16	0.043	x	x
	50.8	2	17	0.05	x	x
50	53	2	17	0.054	x	x

	63.5	2	18	0.076	x	x
65	73	2	21	0.1	x	x
	76	2	21	0.128	x	x
80	84	2	20	0.2	x	x
100	104	2	24	0.3	x	x
125	129	2	34	0.4	x	x
150	154	2	41	0.5	x	x
200	204	2	50	0.9	x	x
254	254	2	55	1.3	x	x
300	304	2	68	2.2	x	x
350	354	2	84	3	x	x
400	354	3	96	4.7	x	x
450	406	3	106	6.3	x	x
500	506	3	120	7.2	x	x