

Special perforated sheets

The standard dimensions in stock are 2000 x 1000, in different thicknesses and perforations.

Other sizes, lower and higher, can be manufactured on demand, being able to reach formats of 4000 x 2000 mm in some thicknesses and perforations.

Finishes: 2B.



Technical information

DIMENSIONES										
Chapa 2000 x 1000 AISI-304										
Elementos estándar										Espesor
Descripción	perforación mm	distancia entre centros	% coeficiente perforación	0.5	0.60	0.8	3	6	5	7
redondo 60°	0.50	18264	10	*						
redondo 60°	0.60	18264	15							
redondo 60°	0.80	27395	20	*	*					
redondo 60°	1	2	23	*		*				
redondo 60°	43831	18295	20			*				
redondo 60°	18264	3	23			*	*	*		
redondo 60°	2	18323	30				*	*		
redondo 60°	18295	4	18				*	*		
redondo 60°	3	5	33						*	
redondo 60°	4	7	33					*	*	*
redondo 60°	5	8	35					*	*	*
redondo 60°	6	10	33					*	*	*
redondo 60°	8	12	40						*	*
redondo 60°	10	15	40					*	*	*
redondo 60°	12	17	45					*	*	*
redondo 60°	15	22	42					*	*	*

