

Long round perforated sheets

The standard dimensions in stock are 2000 x 1000, in different thicknesses and perforations.

Other sizes, lower and higher, can be manufactured on demand, being able to reach formats of 4000 x 2000 mm in some thicknesses and perforations.

Finishes: 2B.



Technical information

| DIMENSIONES | | | | | | | | | | | |
|-------------------------------|----------------|-------------------------|---------------------------|-----|------|-----|-----|-----|-----|---------|------------|
| Chapa 2000 x 1000 AISI-304 | | | | | | | | | | | |
| Elementos estándar | | | | | | | | | | Espesor | |
| Descripción | perforación mm | distancia entre centros | % coeficiente perforación | 0.5 | 0.60 | 0.8 | 365 | 264 | 454 | 1336557 | 3658636617 |
| redondo 60° | 0.50 | 18264 | 10 | * | | | | | | | |
| redondo 60° | 0.60 | 18264 | 15 | | | | | | | | |
| redondo 60° | 0.80 | 27395 | 20 | * | * | | | | | | |
| redondo 60° | 1 | 2 | 23 | * | | * | | | | | |
| redondo 60° | 43831 | 18295 | 20 | | | * | | | | | |
| redondo 60° | 18264 | 3 | 23 | | | * | * | * | | | |
| redondo 60° | 2 | 18323 | 30 | | | * | * | | | | |
| redondo 60° | 18295 | 4 | 18 | | | * | * | | | | |
| redondo 60° | 3 | 5 | 33 | | | | | | | * | |
| redondo 60° | 4 | 7 | 33 | | | | | * | * | * | |
| redondo 60° | 5 | 8 | 35 | | | | | * | * | * | |
| redondo 60° | 6 | 10 | 33 | | | | | * | * | * | |
| redondo 60° | 8 | 12 | 40 | | | | | * | * | * | |
| redondo 60° | 10 | 15 | 40 | | | | | * | * | * | |
| redondo 60° | 12 | 17 | 45 | | | | | * | * | * | |
| redondo 60° | 15 | 22 | 42 | | | | | * | * | * | |

