

## Stainless Steel Locks with Key and Latch-Type Knobs

### BOCK safety lock

- AISI-303 stainless steel closure male.
- AISI-303 stainless steel guide shaft.
- Hexagon nut wrench 24 made of AISI-303 stainless steel
- Flat elastic washer, elastic pin Ø 3 x 20 mm and compensation spring in stainless steel.
- Models for opening to the right, -D and to the left -S, the fittings are supplied disassembled as they are adaptable to various door thicknesses.

### CQ safety lock

- AISI-304 stainless steel closure male.
- AISI-304 stainless steel guide shaft.
- Lever and closure in AISI-304 stainless steel, 4 mm thick.
- Assembly with M-22x1.5 hexagon nut.
- 90° rotation.
- Technopolymer key with polyamide socket.

CQ/A model with 2 wings in keyhole.

CQ/T model with triangle in keyhole.

### VCK closing handwheel

- VC type steering wheel in black duroplastic, finish resistant to solvents, oils, greases and other chemical agents.
- AISI-303 stainless steel smooth stud.
- Helical closing cam made of AISI 316L sintered steel with pre-hole for fixing with a pin.
- Elastic pin Ø 3 x 20 mm.
- Door thickness compensation spring in AISI-302 stainless steel.

Models for opening on the right, -D and on the left -S

