

Bend 45° Male-Female

Manufacturing standards: DVGW round tubes manufactured according to DIN-1988/2463 EN 10312 Tubes with DVGW TS 225 approval correspond to the requirements of DVGW worksheet W 541

Certificates: Standard supply in lengths of 6 m. We provide product certificates if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

Grades: Austenitic grades types 304-L, 316-L

Dimensions: Manufactured in diameters from 15 mm to 108 mm. Wall thicknesses from 1 to 2 mm

Applications: DVGW W 541 tubes are used in the transport of drinking and chlorinated water up to 2 mg/l in water with AISI-316 L pipes, AISI-304 L quality is used in compressed air installations.



Technical information

| DN | Dimensiones | | | Art. |
|-----|-------------|-----|-----|------|
| | Tubo Ø | L | L1 | |
| 15 | 15 | 45 | 36 | 0702 |
| 15 | 18 | 42 | 37 | 0703 |
| 20 | 22 | 52 | 42 | 0704 |
| 25 | 28 | 56 | 48 | 0705 |
| 32 | 35 | 53 | 43 | 2706 |
| 40 | 42 | 61 | 51 | 2707 |
| 50 | 54 | 73 | 62 | 2708 |
| 65 | 76,1 | 111 | 97 | 2709 |
| 80 | 88,9 | 13 | 112 | 2710 |
| 100 | 108 | 157 | 139 | 2711 |