

ELECTRODO OK 48.00 ESAB

OK 48.00 is a low hydrogen electrode, reliable for general and demanding applications for mild and low alloy steels. OK 48.00 is an all-position electrode that offers a stable and smooth arc with reliable and homogeneous mechanical properties. It guarantees all the welds you have to make, from root to fill regardless of the thickness or welding conditions of the job.

| **Approvals:** | ABS; 3Y H5; BV; 3Y H5; EC; EN 13479; DB; 10.039.12; DNV-GL; 3 YH5; LR; 3Ym H5; PRS; 3Y H5; FIGHT; 3Y H5; RS; 3Y H5; VdTÜV; 00690; NAKS/HAKC; 2.0-5.0mm

| **Ratings:** | SFA/AWS A5.1; E7018 H4 R; EN ISO 2560-A; E 42 4 B 42 H5



Technical information

CODIGO	DESCRIPCION
60010148002535	ELECTRODE BASIC O.K. 48.00 DE 2,50.350MM
60010148003235	ELECTRODE BASIC O.K. 48.00 DE 3,2.350MM
60010148003245	ELECTRODE BASIC O.K. 48.00 DE 3,25.450MM
60010148004045	ELECTRODE BASIC O.K. 48.00 DE 4,00.450MM
60010148005045	ELECTRODE BASIC O.K. 48.00 DE 5,0.450MM