


## Hexagon Bushing, Male-Female (Fig. 241)

**Thread Type:** Compatible with ISO 7 / 1.

**Finish:** Polished and matte

**Quality:** They are manufactured in bar, tube or microfusion of AISI-316 stainless steel.



### Technical information

| Ø                   |       |             | Pulida |         | Mate |         |          |
|---------------------|-------|-------------|--------|---------|------|---------|----------|
| Nominal en Pulgadas | D     |             | L      | S Exago | L    | S Exago | Peso kgs |
| 1/4"                | 13.5  | Ø reducción | 18     | 17      | 19   | 16      | 0.015    |
| 3/8"                | 17.2  | Ø reducción | 19     | 20      | 19   | 19      | 0.02     |
| 1/2"                | 21.3  | Ø reducción | 21     | 24      | 22   | 23      | 0.036    |
| 3/4"                | 26.9  | Ø reducción | 23     | 30      | 26   | 28      | 0.047    |
| 1"                  | 33.7  | Ø reducción | 26     | 35      | 28   | 36      | 0.076    |
| 1 1/4"              | 42.4  | Ø reducción | 29     | 44      | 33   | 46      | 0.142    |
| 1 1/2"              | 48.3  | Ø reducción | 33     | 48      | 35   | 50      | 0.146    |
| 2"                  | 60.3  | Ø reducción | 37     | 61      | 39   | 65      | 0.314    |
| 2 1/2"              | 76.1  | Ø reducción | 42     | 78      | 46   | 80      | 0.632    |
| 3"                  | 88.9  | Ø reducción | 43     | 90      | 48   | 92      | 0.802    |
| 4"                  | 114.3 | Ø reducción | -      | -       | -    | -       | -        |