

## Knurled fixing controls BT.S / BT.S-p-INOX

### BT.S-p-INOX

Knurled fixing controls. Polyamide-based technopolymer (PA). Resistant to solvents, oils, greases and other chemical agents

[Catalog access](#)

Image not found or type unknown



### Technical information

Elementos standard		Dimensiones principales						Agujero de montaje		Peso	
Código	Código	Descripción	D	L	d1	d2	l2	d 6H	h	g	
	106521	BT.20 S-M5-INOX	20	16	11.5	11	6	M5	5	6	
	106621	BT.25 S-M6-INOX	25	19	16	15	8	M6	8	9	
	106721	BT.32 S-M8-INOX	32	22	17	21	9	M8	10	12	

Elementos standard			Dimensiones principales				Espárrago roscado		Peso	
Código	Código	Descripción	D	L	d1	d2	I2	d 6H	h	g
	106541	BT.20 S-p-M5x10-INOX	20	16	11.5	11	6	M5	10	7
	106542	BT.20 S-p-M5x16-INOX	20	16	11.5	11	6	M5	16	8
	106642	BT.25 S-p-M6x16-INOX	25	19	16	15	8	M6	16	10
	106644	BT.25 S-p-M6x20-INOX	25	19	16	15	8	M6	20	11
	106647	BT.25 S-p-M6x30-INOX	25	19	16	15	8	M6	30	13
	106752	BT.32 S-p-M8x16-INOX	32	22	17	21	9	M8	16	17
	106754	BT.32 S-p-M8x20-INOX	32	22	17	21	9	M8	20	19
	106757	BT.32 S-p-M8x30-INOX	32	22	17	21	9	M8	30	23