

Knurled controls with DIN 653-NI threaded stud

DIN 653-NI

Knurled controls with threaded stud in stainless steel with a matte shot-peened finish.

[Catalog access](#)

Image not found or type unknown



Technical information

| Elementos standard | | Dimensiones principales | | Espárrago roscado | Peso | |
|--------------------|------------------|-------------------------|-----|-------------------|------|---|
| Código | Descripción | D | L | d | l | g |
| | DIN 653-M4-8-N1 | 16 | 3.5 | M4 | 8 | 6 |
| | DIN 653-M4-10-N1 | 16 | 3.5 | M4 | 10 | 6 |
| | DIN 653-M4-12-N1 | 16 | 3.5 | M4 | 12 | 7 |
| | DIN 653-M4-16-N1 | 16 | 3.5 | M4 | 16 | 7 |

| | | | | | | |
|--------------|-------------------|----|---|-----|----|----|
| | DIN 653-M5-10-N1 | 20 | 4 | M5 | 10 | 11 |
| | DIN 653-M5-12-N1 | 20 | 4 | M5 | 12 | 12 |
| 44310GN29843 | DIN 653-M5-16-N1 | 20 | 4 | M5 | 16 | 12 |
| | DIN 653-M5-20-N1 | 20 | 4 | M5 | 20 | 13 |
| | DIN 653-M6-12-N1 | 24 | 5 | M6 | 12 | 20 |
| 44310GN29847 | DIN 653-M6-16-N1 | 24 | 5 | M6 | 16 | 21 |
| 44310GN29848 | DIN 653-M6-20-N1 | 24 | 5 | M6 | 20 | 22 |
| | DIN 653-M6-25-N1 | 24 | 5 | M6 | 25 | 23 |
| | DIN 653-M8-16-N1 | 30 | 6 | M8 | 16 | 37 |
| | DIN 653-M8-20-N1 | 30 | 6 | M8 | 20 | 39 |
| | DIN 653-M8-25-N1 | 30 | 6 | M8 | 25 | 40 |
| 44310GN29856 | DIN 653-M8-30-N1 | 30 | 6 | M8 | 30 | 42 |
| | DIN 653 M10-20-N1 | 36 | 8 | M10 | 20 | 72 |
| | DIN 653 M10-25-N1 | 36 | 8 | M10 | 25 | 74 |
| | DIN 653 M10-30-N1 | 36 | 8 | M10 | 30 | 76 |
| | DIN 653 M10-40-N1 | 36 | 8 | M10 | 40 | 80 |
| | | | | | | |