

Sliding Sleeve


Manufacturing standards: DVGW round tubes manufactured according to DIN-1988/2463 EN 10312 Tubes with DVGW TS 225 approval correspond to the requirements of DVGW worksheet W 541

Certificates: Standard supply in lengths of 6 m. We provide product certificates if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

Grades: Austenitic grades types 304-L, 316-L

Dimensions: Manufactured in diameters from 15 mm to 108 mm. Wall thicknesses from 1 to 2 mm

Applications: DVGW W 541 tubes are used in the transport of drinking and chlorinated water up to 2 mg/l in water with AISI-316 L pipes, AISI-304 L quality is used in compressed air installations.



Technical information

| DN | Dimensiones | | Art. |
|-----|-------------|-----|------|
| | Tubo Ø | L | |
| 12 | 15 | 80 | 2102 |
| 15 | 18 | 80 | 2103 |
| 20 | 22 | 84 | 2104 |
| 25 | 28 | 91 | 2105 |
| 32 | 35 | 102 | 2106 |
| 40 | 42 | 120 | 2107 |
| 50 | 54 | 140 | 2108 |
| 65 | 76,1 | 230 | 2109 |
| 80 | 88,9 | 260 | 2110 |
| 100 | 108 | 310 | 2111 |