


Machine feet Type M

Type M

Its design is conveniently rounded to facilitate cleaning, the embedded rubber is approved for food products (FDA), and can absorb up to 5° of unevenness in the floor and equipment.



Technical information

| Base | | | | | | |
|-------------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Código | Descripción | Diámetro Ø | Altura B | Carga nom. | | |
| 44310M40 | M 40 | 40 mm | 20 mm | 2.500 N | | |
| 44310M50 | M 50 | 50 mm | 21 mm | 4.000 N | | |
| 44310M75 | M 75 | 75 mm | 22 mm | 10.000 N | | |
| | M 100 | 100 mm | 32 mm | 22.000 N | | |
| 44310M105 | M 105 | 100 mm | 30 mm | 12.000 N | | |
| 44310M125 | M 125 | 125 mm | 37 mm | 30.000 N | | |
| 44310M150 | M 150 | 150 mm | 40 mm | 45.000 N | | |
| | M 180 | 180 mm | 40 mm | 50.000 N | | |
| Espárrago roscado | | | | | | |
| Longitud | Diámetro Ø | | | | | |
| | Ø 10 | Ø 12 | Ø 14 | Ø 16 | Ø 20 | Ø 24 |
| 50 mm | | | | | | |
| 70 mm | | | | | | |
| 83 mm | 44310ME10083 | 44310ME12083 | 44310ME14083 | 44310ME16083 | | |
| 100 mm | 44310ME10100 | 44310ME12100 | | 44310ME16100 | 44310ME20100 | 44310ME24100 |
| 150 mm | | 44310ME12150 | | 44310ME16151 | 44310ME20150 | 44310ME24150 |
| 180 mm | | | | | | |

| | | | | | | |
|--------|--|--|--|--|--|--|
| 230 mm | | | | | | |
| 310 mm | | | | | | |