

## Eccentric Reducers, Metric

**Manufacturing Standards:** Welded millimetric components are manufactured according to DIN-2605/17457 standards.

**Grade:** Austenitic, series 304, 316, 304-L, 316-L.

**Finishes:** Standard finish 2B demand, satin or polished.

**Dimensions:** Manufactured in diameters from 18 mm to 506 mm.

**Certificates:** Product certificates provided, if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

Image not found or type unknown



### Technical information

Dimensiones				Peso kgs	Calidades	
D	d	e	L		AISI-304L	AISI-316L
23	20	1.5	40	0.019378659520204	x	x
25		1.5	40	0.021063760348048	x	x
28		1.5	40	0.023591411589814	x	x
33		1.5	50	0.033480646638917	x	x
38		1.5	60	0.045278756449355	x	x
43		1.5	70	0.058977626235039	x	x
25	23	1.5	40	0.021732452438692	x	x

28		1.5	40	0.024340346731335	x	x
33		1.5	50	0.034217200531218	x	x
38		1.5	60	0.046003082855235	x	x
43		1.5	70	0.059691057753885	x	x
50.8		1.5	75	0.075079843156032	x	x
53		1.5	75	0.078331332426569	x	x
63.5		1.5	80	0.098799950858619	x	x
28	25	1.5	40	0.021732452438692	x	x
33		1.5	40	0.024340346731335	x	x
38		1.5	50	0.034217200531218	x	x
43		1.5	60	0.046003082855235	x	x
50.8		1.5	70	0.059691057753885	x	x
53		1.5	75	0.075079843156032	x	x
63.5		1.5	75	0.078331332426569	x	x
73		1.5	80	0.098799950858619	x	x
33	28	1.5	50	0.035628407634718	x	x
38		1.5	60	0.047402338560641	x	x
43		1.5	70	0.061076815989781	x	x
50.8		1.5	75	0.076619576386823	x	x
53		1.5	75	0.079937747017749	x	x
63		1.5	80	0.10060153555835	x	x
73		1.5	90	0.1296307499389	x	x
76		1.5	90	0.13495804103228	x	x
84		2	90	0.19888553415283	x	x
104		2	110	0.29653661958037	x	x
38	33	1.5	60	0.049023533554504	x	x
43		1.5	70	0.062694076656743	x	x
50.8		1.5	75	0.078421524237402	x	x
53		1.5	75	0.081817731979966	x	x
63.5		1.5	80	0.10271488002256	x	x
73		1.5	90	0.13183717376352	x	x
76		1.5	90	0.1372551398086	x	x
84		2	90	0.20227073234952	x	x
104		2	110	0.30002601143238	x	x
43	38	1.5	70	0.064525435023358	x	x
50.8		1.5	75	0.080468073062536	x	x
53		1.5	75	0.083952910872331	x	x
63.5		1.5	80	0.10512118318266	x	x
73		1.5	90	0.13435968404736	x	x
76		2	90	0.18650841986482	x	x

84		2	90	0.20614088511375	x	x
104		2	110	0.30403700581906	x	x
50.8	43	1.5	75	0.082741074695324	x	x
53		1.5	75	0.086324349583704	x	x
63		1.5	80	0.107800828771	x	x
73		1.5	90	0.1371808451052	x	x
76		1.5	90	0.14281841408213	x	x
84		2	90	0.21046924180524	x	x
104		2	110	0.30854926165254	x	x
53	50.8	2	75	0.12060122924919	x	x
63.5		2	80	0.14997325873924	x	x
73		2	90	0.18951392822175	x	x
76		2	90	0.19730217184731	x	x
84		2	90	0.21807082151544	x	x
104		2	110	0.31653771928317	x	x
129		1.5	80	0.11247994405443	x	x
63	53	1.5	80	0.11390103865487	x	x
73		1.5	90	0.14364689054094	x	x
76		1.5	90	0.14955018741249	x	x
84		2	90	0.22038974987104	x	x
104		2	110	0.32	x	x
129		2	132		x	x
154		2	150		x	x
204		2	170		x	x
73	63.5	1.5	90		x	x
76		2	90	0.22	x	x
84		2	90	0.22	x	x
104		2	110	0.23181127986283	x	x
129		2	130		x	x
154		2	150		x	x
204		2	170		x	x
84	73	2	90	0.24	x	x
104		2	110	0.24	x	x
129		2	130	0.34489683523877	x	x
154		2	150	0.24452358703476	x	x
204		2	170	0.34489683523877	x	x
254		2	220		x	x
84	76	2	90	0.24855990068071	x	x
104		2	110	0.349291604666	x	x
129		2	130	0.48796937839884	x	x

154		2	150		x	x
254		2	220	0.5	x	x
104	84	2	110	0.36158082268099	x	x
129		2	130	0.50155261325395	x	x
154		2	150	0.67	x	x
204		2	170		x	x
254		2	220	0.66506360918139	x	x
129	104	2	130	0.53947909675183	x	x
154		2	150	0.7061009285481	x	x
204		2	170	1.0212511380455	x	x
254		2	220	1.5526475614898	x	x
154	129	2	150	0.76534335255137	x	x
204		2	170	1.0935813215803	x	x
254		2	220	1.6272225596095	x	x
304		2	300	2.4937638390102	x	x
204	154	2	170	1.1754623328492	x	x
254		2	220	1.7134410474517	x	x
304		2	300	2.5751587444849	x	x
354		2	350	3.4003243580102	x	x