# Wheels with steel brake Ø 80-200 200-500Kg

**Stainless steel swivel wheels with brake Ø 80-200 200-500Kg**

Stainless steel swivel wheels with brakes. Double row ball swivel bearing, protected, inner bowl of the swivel head reinforced and subjected to heat treatment, riveted swivel head, screwed wheel axle, fixing plate.

nylon hoop

## Technical information

| Código | Descripción | Nº orden | Ø rueda | Ancho Rueda | Med. Pletina | Distan. Agujeros | Ø agujeros | Desplaz. | Altura | Cap. Carga | Precio |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 3416UOO080 | RUEDA Ø080 | | | | | | | | | | 0 |
| 34168477080P62 | SOPORTE 080 | | | | | | | | | | 0 |
| 341612458 | CASQUILLERIA 12x45x8,2 | 8477UOO080P62 | 80 | 34 | 105X85 | 80/77 X 60 | 9 | 44.5 | 108 | 200 | 0 |
| 1401093408 | DIN-934 M-8 | | | | | | | | | | 0 |
| 1401093308060 | DIN-933 M-8.60 | | | | | | | | | | 0 |

| Código | Descripción | Nº orden | Ø rueda | Ancho Rueda | Med. Pletina | Distan. Agujeros | Ø agujeros | Desplaz. | Altura | Cap. Carga | Precio |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 3416UOO100 | RUEDA Ø 100 | | | | | | | | | | 0 |
| 34168477100P62 | SOPORTE 100MM | | | | | | | | | | 0 |
| 341612458 | CASQUILLERIA 12x45x8,2 | 8477UOO100P62 | 100 | 36 | 105X85 | 80/77 X 60 | 9 | 41 | 128 | 200 | 0 |
| 1401093408 | DIN-934 M-8 | | | | | | | | | | 0 |
| 1401093308060 | DIN-933 M-8.60 | | | | | | | | | | 0 |

| Código | Descripción | Nº orden | Ø rueda | Ancho Rueda | Med. Pletina | Distan. Agujeros | Ø agujeros | Desplaz. | Altura | Cap. Carga | Precio |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 3416UOO125 | RUEDA Ø125 | | | | | | | | | | 0 |
| 34168477125P62 | SOPORTE 125MM | | | | | | | | | | 0 |

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 341612458 | CASQUILLERIA 12x45x8,2 | 8477UOO125P62 | 125 | 40 | 105X85 | 80/77 X 60 | 9 | 40 | 155 | 200 | 0 |
| 1401093408 | DIN-934 M-8 | | | | | | | | | | 0 |
| 1401093308060 | DIN-933 M-8.60 | | | | | | | | | | 0 |

| Código | Descripción | Referencia | Ø rueda | Ancho Rueda | Med. Pletina | Distan. Agujeros | Ø agujeros | Desplaz. | Altura | Cap. Carga | Precio |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | RUEDA Ø125 | | | | | | | | | | 0 |
| 34168477125P62 | SOPORTE 125MM | | | | | | | | | | 0 |
| 341612458 | CASQUILLERIA 12x45x8,2 | 8477UOO125P63 | 125 | 40 | 137X105 | 105 X 80/75 | 11 | 55 | 161 | 300 | 0 |
| 1401093408 | DIN-934 M-8 | | | | | | | | | | 0 |
| 1401093308060 | DIN-933 M-8.60 | | | | | | | | | | 0 |

| Código | Descripción | Nº orden | Ø rueda | Ancho Rueda | Med. Pletina | Distan. Agujeros | Ø agujeros | Desplaz. | Altura | Cap. Carga | Precio |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 341575873 | RUEDA Ø160 | | | | | | | | | | 0 |
| | SOPORTE 160MM | | | | | | | | | | 0 |
| | CASQUILLERIA Ø20x60xØ13 | 8477UOO160P63 | 160 | 40 | 137X105 | 105 X 80/75 | 9 | 60 | 200 | 500 | 0 |
| | DIN-934 M-12 | | | | | | | | | | 0 |
| | DIN-933 M-12.80 | | | | | | | | | | 0 |

| Código | Descripción | Nº orden | Ø rueda | Ancho Rueda | Med. Pletina | Distan. Agujeros | Ø agujeros | Desplaz. | Altura | Cap. Carga | Precio |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 3416UOO20046 | RUEDA Ø200 | | | | | | | | | | 0 |
| 34168477200P63 | SOPORTE200MM | | | | | | | | | | 0 |
| 341612459 | CASQUILLERIA Ø20x60xØ13 | 8477UOO200P63 | 200 | 50 | 137X105 | 105 X 80/75 | 9 | 55 | 240 | 500 | 0 |
| 1401093412 | DIN-934 M-12 | | | | | | | | | | 0 |
| 1401093312080 | DIN-933 M-12.80 | | | | | | | | | | 0 |