

Wheels turning in steel with central support Ø 80-125 150KG

Stainless steel swivel wheels with central support Ø 80-125 150KG

Stainless steel swivel wheels with central support. Double row ball swivel bearing, through hole.

Nylon wheel rim with anti-thread plate and smooth hub.



Technical information

Código	Descripción	Nº orden	Ø rueda	Ancho Rueda	Agujero pasante (mm)	Desplaz.	Altura	Cap. Carga	Precio
3416UOO080	RUEDA Ø080	8470UOO080P30-11	80	34	M12	44.5	108	150	0
34168470080P30	SOPORTE 080								0
341612458	CASQUILLERIA 12x45x8,2								0
1401093408	DIN-934 M-8								0
1401093308060	DIN-933 M-8.60								0
Código	Descripción	Nº orden	Ø rueda	Ancho Rueda	Agujero pasante (mm)	Desplaz.	Altura	Cap. Carga	Precio
3416UOO100	RUEDA Ø 100	8470UOO100P30-11	100	36	M12	41	128	150	0
34168470100P30	SOPORTE 100MM				11				0
341612458	CASQUILLERIA 12x45x8,2								0
1401093408	DIN-934 M-8								0
1401093308060	DIN-933 M-8.60								0
Código	Descripción	Nº orden	Ø rueda	Ancho Rueda	Agujero pasante (mm)	Desplaz.	Altura	Cap. Carga	Precio
3416UOO125	RUEDA Ø125	8470UOO125P30-11	125	40	M12	40	155	150	0

34168470125P30	SOPORTE 125MM				11				0
341612458	CASQUILLERIA 12x45x8,2								0
1401093408	DIN-934 M-8								0
1401093308060	DIN-933 M-8.60								0