

Female Threaded Tee


Manufacturing standards: DVGW round tubes manufactured according to DIN-1988/2463 EN 10312 The tubes with the DVGW TS 225 approval correspond to the requirements of the DVGW W 541 worksheet

Certificates: Standard supply in lengths of 6 meters We provide product certificates if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

Grades: Austenitic grades types 304-L, 316-L

Dimensions: Manufactured in diameters from 15 mm to 108 mm. Wall thicknesses from 1 to 2 mm

Applications: The DVGW W 541 tubes are used in the transport of drinking water and chlorinated up to 2 mg/l in the water with AISI-316 L pipes, the quality AISI-304 L is used in compressed air installations.



Technical information

DN	Dimensiones	L	L1	Art.
	Tubo Ø			
12-15	15-1/2"-15	64	40	1304
15	18-1/2"-18	68	42	1305
15-20	18-3/4"-18	68	44	1306
20-15	22-1/2"-22	74	43	1307
20	22-3/4"-22	74	46	1308
25-15	28-1/2"-28	84	46	1309
25-20	28-3/4"-28	84	49	1310
25	28-1/2"-28	84	5	1311
32-15	35-1/2"-35	100	50	1312
32-20	35-3/4"-35	100	53	1313
40-15	42-1/2"-42	114	53	1316
40-20	42-3/4"-42	114	56	1317
50-15	54-1/2"-54	138	59	1320
50-20	54-3/4"-54	138	62	1321
50	54-2"-54	138	79	1324
65-20	76,1-3/4"-76,1	230	79	1326

65-50	76,1-2"-76,1	230	89	1329
80-20	88,9-3/4"-88,9	260	88	1331
80-50	88,9-2"-88,9	260	96	1334
100-25	104-3/4"-104	310	105	1336
100-50	104-2"-104	310	115	1339