

## Sanitary Piping/Tubing (Food Industry)

- **Manufacturing Standards:** Millimetric round tubes manufactured according to DIN-11850, SMS 3008 and ASTM A-270 - EN 10217-7
- **Grade:** Austenitic, series 304-L, 316-L
- **Coating:** polished or satin tubes are plastic coated.
- **Finish:** Finished with ridges on the surface according to welding standards suitable for the food industry products. We have finished pipe, matte and polished internally and /or externally.
- **Certificates:** Product certificates provided if required, according to the following standard: EN 10204/3.1.B or DIN 50049.
- **Dimensions:** Manufactured in diameters from 12 mm to 154 mm. Wall thicknesses of 1 to 2 mm.



### Technical information

Pulgadas NW	Diam. Ext. mm.	Espesor mm.	Peso kg/mts	304	Calidades 304L	AISI 316	316L
NW10	12	1	0.27	*			*
1/2"	12.7	1.25	0.36	*			*
NW15	18	1	0.43	x	x	x	x
3/4"	17.15	1.25	0.54	*			*
3/4"	17.15	1.63	0.71	*			*
NW20	22	1	0.53	x	x	x	x
1"	25.4	1.25	0.73	*			*
1"	25.4	1.63	0.96	*			*
NW25	28	1	0.7	x	x	x	x
1 1/4"	31.75	1.63	0.92	*			*
1 1/4"	31.75	1.63	1.22	*			*
NW32	34	1	0.83	x	x	x	x
NW32	34	1.5	1.38	*			*
1 1/2"	38.1	1.25	1.12	*			*
1 1/2"	38.1	1.63	1.48	*			*
NW40	40	1.5	1.45	x			*
2"	50.8	1.25	1.5	*			*

2"	50.8	1.5	1.85	*			*
2"	50.8	1.99	1.99	*			*
NW50	52	1	1.81	*			*
NW50	52	1.5	1.9	x	x	x	x
2 1/2"	63.5	1.5	2.33	*			*
2 1/2"	63.5	1.63	2.51	*			*
NW65	70	1.5	2.57	*			
NW65	70	2	3.4	x	x	x	x
2 1/2"	76.1	1.5	2.8	*			*
3"	76.1	1.63	3.02	*			*
3"	85	1.5	3.14	*			
NW80	85	2	4.2	x	x	x	x
4"	101.6	2	5.02	*			*
NW100	104	2	5.14	x	x	x	*
NW125	129	2	6.4	x	x	x	x
NW150	154	2	7.66	x	x	x	x
<b>X = stock disponible</b>	<b>* = previa demanda</b>						
<b>X = available stock</b>	<b>* = upon request</b>						
<b>X = stock disponible</b>	<b>* = sur demande</b>						