

Collars, Metric

Manufacturing Standards: Welded millimetric components are manufactured according to DIN-2605/17457 standards.


Grade: Austenitic, series 304, 316, 304-L, 316-L.

Finishes: Standard finish 2B demand, satin or polished.

Dimensions: Manufactured in diameters from 18 mm to 506 mm.

Certificates: Product certificates provided, if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

Image not found or type unknown



Technical information

DN	Dimensiones				Peso kgs	Calidades	
	D	E	A	H		AISI-304L	AISI-316L
15	18	1.5	45	6	0.024	x	x
15	20	1.5	45	6		x	x
20	23	1.5	58	6.5	0.039	x	x
20	25	1.5	58	7.5		x	x
25	28	1.5	68	7.5	0.054	x	x
25	30	1.5	68	8		x	x
25	33	1.5	68	9		x	x
32	38	1.5	78	9	0.069	x	x
40	43	1.5	88	9	0.087	x	x
50	50.8	1.5	102	10	0.108	x	x
50	53	1.5	102	10		x	x

50	63.5	1.5	102			x	x
65	73	1.5	122	12	0.149	x	x
65	76	1.5	122	12		x	x
80	84	2	138	12	0.191	x	x
100	104	2	158	12	0.227	x	x
125	129	2	188	15	0.31	x	x
150	154	2	212	15	0.35	x	x
200	204	2	268	15	0.5	x	x
254	254	2	320	15	0.6	x	x
300	304	2	365	18	0.7	x	x
350	354	2	415	21	0.85	x	x
400	406	3	482	21	1.85	x	x
450	456	3	535	45	3	x	x
500	506	3	585	45	3.36	x	x