

## Very resistant plastic hinges reinforced with CFT fiberglass.

Very resistant plastic hinges reinforced with CFT fiberglass.

[Catalog access](#)

Very resistant plastic hinges reinforced with CFT fiberglass.

### Technical information

| Código      | Elementos standard | Descripción      | Dimensiones principales |    |      |    |      |      |      |   | Agujero roscado |      |    |     |     | Peso<br>g |          |
|-------------|--------------------|------------------|-------------------------|----|------|----|------|------|------|---|-----------------|------|----|-----|-----|-----------|----------|
|             |                    |                  | L                       | B  | f    | f1 | H    | h1   | b1   | d | d3              | d4   | h3 | h4  | d6  |           | C [Nm] # |
| 427111-C9   | CFT.40 EH-4-C9     | CFT.40 EH-4-C9   | 39.5                    | 38 | 25   | 25 | 13   | 9    | 17.5 | 3 | 4.5             | -    | 4  | -   | 7   | 2         | 11       |
| 427112-C9   | CFT.40 SH-4-C9     | CFT.40 SH-4-C9   | 39.5                    | 38 | 25   | 25 | 13   | 9    | 17.5 | 3 | 4.5             | 8.5  | -  | 4.5 | -   | 2         | 11       |
| 427131-C9   | CFT.49 EH-5-C9     | CFT.49 EH-5-C9   | 49.5                    | 48 | 30.5 | 31 | 16.5 | 11.5 | 21.5 | 4 | 5.5             | -    | 5  | -   | 8.5 | 2         | 24       |
| 427132-C9   | CFT.49 SH-5-C9     | CFT.49 SH-5-C9   | 49.5                    | 48 | 30.5 | 31 | 16.5 | 11.5 | 21.5 | 4 | 5.5             | 10.5 | -  | 5   | -   | 2         | 24       |
| 427133-C9 * | CFT.49 EH-6-C9 *   | CFT.49 EH-6-C9 * | 49.5                    | 48 | 30.5 | 31 | 16.5 | 11.5 | 21.5 | 4 | 6.5             | -    | 5  | -   | 10  | 2         | 24       |
| 427151-C9   | CFT.65 EH-6-C9     | CFT.65 EH-6-C9   | 65                      | 63 | 40   | 40 | 21.5 | 15   | 29   | 5 | 6.5             | -    | 7  | -   | 10  | 2         | 50       |
| 427152-C9   | CFT.65 SH-6-C9     | CFT.65 SH-6-C9   | 65                      | 63 | 40   | 40 | 21.5 | 15   | 29   | 5 | 6.5             | 12.5 | -  | 7.5 | -   | 2         | 50       |