

Elbows, Metric

Manufacturing Standards: Welded millimetric components are manufactured according to DIN-2605/17457 standards.


Grade: Austenitic, series 304, 316, 304-L, 316-L.

Finishes: Standard finish 2B demand, satin or polished.

Dimensions: Manufactured in diameters from 18 mm to 506 mm.

Certificates: Product certificates provided, if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

Image not found or type unknown



Technical information

DN	Dimensiones			Peso kgs	Calidades	
	D	E	R		AISI-304L	AISI-316L
15	18	1.5	27	0.02	x	x
15	20	1.5	30	0.03	x	x
20	23	1.5	35	0.04	x	x
20	25	1.5	38	0.04	x	x
25	28	1.5	42	0.06	x	x
25	30	1.5	45	0.05	x	x
25	33	1.5	50	0.08	x	x
32	38	1.5	57	0.11	x	x
40	40	1	60	0.08	x	x
40	43	1.5	65	0.15	x	x
40	44	2	51	0.21	x	x

50	50.8	1.5	75	0.22	x	x
50	53	1.5	80	0.26	x	x
50	63.5	1.5	95	0.34	x	x
65	73	1.5	110	0.46	x	x
65	76	1.5	114	0.5	x	x
80	84	2	126	0.75	x	x
100	104	2	156	1.2	x	x
125	129	2	194	1.9	x	x
150	154	2	231	2.75	x	x
200	204	2	360	4.8	x	x
254	254	2	381	7.4	x	x
300	304	2	456	9.5	x	x
350	354	2	531	14	x	x
400	406	3	500	23.78	x	x
450	456	3	550	29.4	x	x
500	506	3	600	35.5	x	x