

## ELECTRODE OK 61.30 ESAB 308L

OK 61.30 is an extra-low carbon LMA (low moisture absorption) coated electrode for welding 19Cr10Ni type steels, also suitable for stabilized steels of similar composition, except when the creep resistance of the material must also be satisfied. base. OK 61.30 produces excellent looking weld beads and self-removing slag.

| **Approvals:** | ABS; Stainless; EC; EN 13479; CWB; CSA W48: E308L-17; DB; 30.039.02; DNV-GL; VL 308 L; NAKS/HAKC; 2.0-4.0mm; Seproz; A 272580; VdTÜV; 00792

| **Ratings:** | EN ISO 3581-A; E 19 9 L R 1 2; SFA/AWS A5.4; E308L-17; CSA W48; E308L-17; Werkstoffnummer; 1.4316



### Technical information

CODIGO	DESCRIPCION
60010161301630	ELECTRODE INOX. 308L O.K. 61.30 1,60.300MM
60010161302030	ELECTRODE INOX. 308L O.K. 61.30 2,00.300MM
60010161302530	ELECTRODE INOX. 308L O.K. 61.30 2,50.300MM
60010161303235	ELECTRODE INOX. 308L O.K. 61.30 3,25.350MM
60010161304035	ELECTRODE INOX. 308L O.K. 61.30 4,00.350MM