

Knurled fixing controls BT.S / BT.S-p-INOX

BT.S-p-INOX

Knurled fixing controls. Polyamide-based technopolymer (PA). Resistant to solvents, oils, greases and other chemical agents

[Catalog access](#)

Image not found or type unknown



Technical information

| Elementos standard | | Dimensiones principales | | | | | | Agujero de montaje | | Peso | |
|--------------------|--------|-------------------------|----|----|------|----|----|--------------------|----|------|--|
| Código | Código | Descripción | D | L | d1 | d2 | l2 | d 6H | h | g | |
| | 106521 | BT.20 S-M5-INOX | 20 | 16 | 11.5 | 11 | 6 | M5 | 5 | 6 | |
| | 106621 | BT.25 S-M6-INOX | 25 | 19 | 16 | 15 | 8 | M6 | 8 | 9 | |
| | 106721 | BT.32 S-M8-INOX | 32 | 22 | 17 | 21 | 9 | M8 | 10 | 12 | |

| Elementos standard | | | Dimensiones principales | | | | Espárrago roscado | | Peso | |
|--------------------|--------|----------------------|-------------------------|----|------|----|-------------------|------|------|----|
| Código | Código | Descripción | D | L | d1 | d2 | I2 | d 6H | h | g |
| | 106541 | BT.20 S-p-M5x10-INOX | 20 | 16 | 11.5 | 11 | 6 | M5 | 10 | 7 |
| | 106542 | BT.20 S-p-M5x16-INOX | 20 | 16 | 11.5 | 11 | 6 | M5 | 16 | 8 |
| | 106642 | BT.25 S-p-M6x16-INOX | 25 | 19 | 16 | 15 | 8 | M6 | 16 | 10 |
| | 106644 | BT.25 S-p-M6x20-INOX | 25 | 19 | 16 | 15 | 8 | M6 | 20 | 11 |
| | 106647 | BT.25 S-p-M6x30-INOX | 25 | 19 | 16 | 15 | 8 | M6 | 30 | 13 |
| | 106752 | BT.32 S-p-M8x16-INOX | 32 | 22 | 17 | 21 | 9 | M8 | 16 | 17 |
| | 106754 | BT.32 S-p-M8x20-INOX | 32 | 22 | 17 | 21 | 9 | M8 | 20 | 19 |
| | 106757 | BT.32 S-p-M8x30-INOX | 32 | 22 | 17 | 21 | 9 | M8 | 30 | 23 |