


## 2-Piece Adapter

- **Manufacturing standards:** DVGW round tubes manufactured according to DIN-1988/2463 EN 10312 Tubes with DVGW TS 225 approval correspond to the requirements of DVGW worksheet W 541
- **Certificates:** Standard supply in lengths of 6 m. We provide product certificates if required, according to the following standard: EN 10204/3.1.B or DIN 50049.
- **Grades:** Austenitic grades types 304-L, 316-L
- **Dimensions:** Manufactured in diameters from 15 mm to 108 mm. Wall thicknesses from 1 to 2 mm
- **Applications:** DVGW W 541 tubes are used in the transport of drinking and chlorinated water up to 2 mg/l in water with AISI-316 L pipes, AISI-304 L quality is used in compressed air installations.



### Technical information

DN	Dimensiones		Art.
	Tubo Ø	L	
12	15-½"	51	5042
12	15-¾"	37	5032
12	15-1¼"	43	5072
15	18-¾"	37	5033
15	18-1½"	44	5043
20	22-1"	40	5034
20	22-1¼"	43	5044
20	22-1½"	44	5045
25	28-1"	40	5046
25	28 1¼"	44	5035
25	28-1½"	46	5036
32	35-1½"	48	5047
40	42-1¼"	52	5037
50	54-2 3/8"	58	5038