

Eccentric welding reduction

- **Manufacturing standards:** Millimeter round tubes manufactured according to DIN-11850, SMS 3008 and ASTM A-270 - EN 10217-7
- **Grades:** Austenitic grades types 304-L, 316-L
- **Protection:** Polished or satin tubes are supplied with plastic coating
- **Finishes:** Finished with roughness according to standards on the surface and welding suitable for the food industry. We have pipes in matte and polished interior and/or exterior finishes.
- **Certificates:** We provide product certificates if required, according to the following standard: EN 10204/3.1.B or DIN 50049.
- **Dimensions:** Manufactured in diameters from 12 mm to 154 mm. Wall thicknesses from 1 to 2 mm



Technical information

NW	D	d	L	Peso	AISI 316
20 – 15	22	18	11	0.02	*
25 – 15	28	18	28	0.02	*
25 – 20	28	22	29	0.01	*
32 – 20	34	22	30	0.03	*
32 – 25	34	28	30	0.04	*
40 – 20	40	22	33	0.04	*
40 – 25	40	28	34	0.05	*
40 – 32	40	34	43	0.07	*
50 – 25	52	28	44	0.08	*
50 – 32	52	34	45	0.11	*
50 – 40	52	40	45	0.07	*
65 – 32	70	34	56	0.19	*
65 – 40	70	40	59	0.17	*
65 – 50	70	52	51	0.11	*
80 – 40	85	40	82	0.23	*
80 – 50	85	52	73	0.21	*

80 – 65	85	70	50	0.14	*
100 – 50	104	52	94	0.8	*
100 – 65	104	70	50	0.34	*
100 – 80	104	85	54	0.2	*
* = previa demanda	* = upon request	* = sur demande			