

## Female Union


**Manufacturing standards:** DVGW round tubes manufactured according to DIN-1988/2463 EN 10312 Tubes with DVGW TS 225 approval correspond to the requirements of DVGW worksheet W 541

**Certificates:** Standard supply in lengths of 6 m. We provide product certificates if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

**Grades:** Austenitic grades types 304-L, 316-L

**Dimensions:** Manufactured in diameters from 15 mm to 108 mm. Wall thicknesses from 1 to 2 mm

**Applications:** DVGW W 541 tubes are used in the transport of drinking and chlorinated water up to 2 mg/l in water with AISI-316 L pipes, AISI-304 L quality is used in compressed air installations.



### Technical information

| DN    | Dimensiones |    | Art. |
|-------|-------------|----|------|
|       | Tubo Ø      | L  |      |
| 12-15 | 15-½"       | 37 | 1802 |
| 12-20 | 15-¾"       | 38 | 1823 |
| 15-15 | 18-½"       | 37 | 1803 |
| 15-20 | 18-¾"       | 38 | 1804 |
| 20-15 | 22-½"       | 36 | 1805 |
| 20-20 | 22-¾"       | 39 | 1806 |
| 20-25 | 22-1"       | 42 | 1824 |
| 25-15 | 28-½"       | 38 | 1807 |
| 25-20 | 28-¾"       | 39 | 1819 |
| 25-25 | 28-1"       | 44 | 1809 |
| 25-32 | 28-1¼"      | 46 | 1825 |
| 32-25 | 35-1"       | 45 | 1820 |
| 32-32 | 35-1¼"      | 49 | 1811 |
| 32-40 | 35-1½"      | 49 | 1826 |
| 40-32 | 42-1¼"      | 51 | 1821 |
| 40-40 | 42-1½"      | 53 | 1814 |

|       |        |    |      |
|-------|--------|----|------|
| 50-40 | 54-1½" | 58 | 1822 |
| 50-50 | 54-2"  | 62 | 1818 |