

## Male Union


**Manufacturing standards:** DVGW round tubes manufactured according to DIN-1988/2463 EN 10312 Tubes with DVGW TS 225 approval correspond to the requirements of DVGW worksheet W 541

**Certificates:** Standard supply in lengths of 6 m. We provide product certificates if required, according to the following standard: EN 10204/3.1.B or DIN 50049.

**Grades:** Austenitic grades types 304-L, 316-L

**Dimensions:** Manufactured in diameters from 15 mm to 108 mm. Wall thicknesses from 1 to 2 mm

**Applications:** DVGW W 541 tubes are used in the transport of drinking and chlorinated water up to 2 mg/l in water with AISI-316 L pipes, AISI-304 L quality is used in compressed air installations.



### Technical information

DN	Dimensiones			Art.
	Tubo Ø	L	L1	
12	15-3/8"	38	18	1726
12-15	15-1/2"	41	21	1703
12-20	15-3/4"	43	23	1714
15-15	15-1/2"	42	22	1704
15-20	18-3/4"	44	24	1705
20-15	22-1/2"	42	21	1715
20-20	22-3/4"	44	23	1707
20-25	22-1"	46	25	1716
25-20	28-3/4"	46	23	1717
25-25	28-1"	48	23	1708
25-32	28-1 ¼"	48	25	1718
32-25	35-1"	51	25	1719
32-32	35-1 ¼"	53	27	1709
32-40	35-1 ½"	53	27	1720
40-32	42-1 ¼"	57	27	1721
40-40	42-1 ½"	57	27	1710

50-40	54-1 ½"	62	27	1722
50-50	54-2"	71	36	1711
65-65	76,1-2 ½"	123	70	1713
80-80	88,9-3"	137	77	1724